


RIFLE

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (fps)	Max Load (Grains)	Max Load Velocity (fps)	Max Load Pressure (psi)	COL (inch)	
220 Swift									
Barrel: 24", Twist: 1-14"			Primer: FED 210		Bullet Diameter .224"				
4064	40	NOS	B-TIP	35.1	3,573	39.0	4,061	58,056	2.680
4064	50	BAR	VAR	35.1	3,381	39.0	3,843	60,180	2.680
4064	55	SIE	BK	33.3	3,138	37.0	3,566	61,596	2.680
2700	40	SIE	BK	42.3	3,884	47.0	4,414	61,000	2.680
2700	50	HDY	V-MAX	42.8	3,793	45.0	4,035	62,500	2.680
2700	55	NOS	B-TIP	41.3	3,602	43.5	3,832	57,000	2.680
2700	60	HDY	V-MAX	39.9	3,391	42.0	3,607	59,700	2.680
2700	63	SIE	SP	39.0	3,458	41.0	3,717	63,400	2.660
2700	70	BRG	HP	37.1	3,229	39.0	3,435	64,000	2.660

223 Winchester Super Short Magnum									
Barrel: 24", Twist: 1-12"			Primer: WIN WLR		Bullet Diameter .224"				
4064	55	NOS	B-TIP	37.8	3,351	42.0	3,723	63,700	2.197
4064	69	SIE	HPBT	35.8	3,069	39.8	3,410	63,800	2.230
2700	55	SIE	BK	43.2	3,465	48.0	3,850	59,600	2.197
2700	69	NOS	HPBT	40.1	3,164	44.5	3,516	62,800	2.230
4350	55	SIE	BK	42.3	3,458	47.0	3,842	59,300	2.197
4350	69	NOS	HPBT	40.1	3,230	44.5	3,589	64,132	2.230

6mm PPC									
Barrel: 24", Twist: 1-14"			Primer: REM 7 1/2		Bullet Diameter .243"				
2015	60	BRG	HP	24.5	2,783	27.2	3,163	49,200	2.050
2015	70	SIE	HPBT	24.3	2,602	27.0	2,957	46,000	2.080
2230	60	BRG	HP	26.6	2,794	29.5	3,175	49,500	2.050
2230	70	BRG	HP	25.7	2,573	28.5	2,924	49,000	2.080
2460	60	SIE	HP	27.0	2,816	30.0	3,200	48,800	2.050
2460	70	BRG	HP	26.6	2,623	29.5	2,981	46,600	2.080
2495	60	SIE	HP	25.7	2,794	28.5	3,175	50,000	2.050

6mm BR Remington									
Barrel: 24", Twist: 1-14"			Primer: FED 205		Bullet Diameter .243"				
2015	58	HDY	V-MAX	27.5	3,055	30.5	3,472	52,700	2.125
2015	70	NOS	B-TIP	27.5	2,887	30.5	3,281	52,900	2.170
2015	80	SIE	BLITZ	26.1	2,679	29.0	3,044	50,200	2.120
2230	60	SIE	HP	30.2	3,008	33.5	3,418	49,400	2.125
2230	70	BRG	HP	29.3	2,865	32.5	3,256	52,500	2.170
2460	60	BRG	HP	31.1	3,082	34.5	3,502	51,600	2.125
2460	70	SIE	HPBT	29.7	2,882	33.0	3,275	51,600	2.170
2495	60	SIE	HP	29.7	2,983	33.0	3,390	46,700	2.125
2495	70	NOS	B-TIP	28.4	2,871	31.5	3,262	50,500	2.170
2520	60	SIE	HP	31.5	3,047	35.0	3,462	50,500	2.125
2520	70	NOS	B-TIP	30.6	2,889	34.0	3,283	51,900	2.170
2520	80	BRG	HP	29.7	2,746	33.0	3,121	51,200	2.120

243 Winchester									
Barrel: 24", Twist: 1-10"			Primer: REM 9 1/2		Bullet Diameter .243"				
2700	55	NOS	B-TIP	43.6	3,364	48.5	3,823	59,118	2.605
2700	58	HDY	V-MAX	41.9	3,225	46.5	3,665	59,944	2.580
2700	70	SIE	BK	40.5	3,078	45.0	3,498	59,118	2.650
2700	80	NOS	B-TIP	39.9	3,039	42.0	3,233	59,472	2.700
2700	85	SIE	SPT	39.0	2,952	41.0	3,140	58,056	2.660
2700	95	HDY	SST	37.1	2,740	39.0	2,915	58,646	2.700
2700	100	SIE	SBT	34.2	2,588	36.0	2,753	56,994	2.700
3100	85	SIE	HPBT	41.4	2,756	46.0	3,132	55,224	2.660
3100	95	NOS	B-TIP	39.6	2,649	44.0	3,010	58,174	2.700
3100	100	SIE	SBT	38.7	2,610	43.0	2,966	59,987	2.700
4350	70	NOS	B-TIP	43.2	3,107	48.0	3,531	56,168	2.650
4350	80	SIE	SPT	39.6	2,918	44.0	3,316	56,522	2.700
4350	87	HDY	V-MAX	39.6	2,899	44.0	3,294	58,764	2.660
4350	95	NOS	B-TIP	36.0	2,680	40.0	3,046	59,826	2.700
4350	100	SIE	SPT	35.1	2,623	39.0	2,981	59,969	2.700

"The ultimate Winchester Super Short Mag powder"



Accurate 2700

Load Density - The perfect combination of case capacity and powder for peak performance.

Performance - For maximum velocities, no other reloading powder comes close. Exceeds factory loads by as much as 200 fps.

RIFLE

Bullet Weight (Grains)	Bullet Make	Bullet Type	Start Load (Grains)	Start Velocity (fps)	Max Load (Grains)	Max Load Velocity (fps)	Max Load Pressure (psi)	COL (inch)	
6mm Remington									
Barrel: 24", Twist: 1-10"			Primer: FED 210M		Bullet Diameter .243"				
4064	55	NOS	B-TIP	40.5	3,547	45.0	4,031	60,180	2.765
4064	60	SIE	HP	40.9	3,432	45.5	3,901	63,600	2.750
4064	65	HDY	V-MAX	40.9	3,290	45.5	3,739	61,500	2.775
4064	70	NOS	B-TIP	40.0	3,235	44.5	3,677	63,200	2.775
2700	55	NOS	B-TIP	45.1	3,445	50.5	3,915	59,944	2.765
2700	58	BAR	VAR	45.5	3,295	50.5	3,744	60,300	2.750
2700	70	SIE	BK	44.1	3,145	49.0	3,574	62,500	2.775
2700	80	SIE	SPT	43.2	3,006	48.0	3,416	62,900	2.825
2700	87	HDY	V-MAX	41.9	2,852	46.5	3,241	59,800	2.810
2700	100	NOS	PART	41.0	2,692	45.5	3,059	61,400	2.825
2700	105	HDY	A-MAX	40.1	2,605	44.5	2,960	60,900	2.825
4350	80	NOS	B-TIP	44.6	2,997	49.5	3,406	61,800	2.825
4350	87	HDY	SP	43.7	2,879	48.5	3,272	62,000	2.810
4350	100	SIE	SBT	41.0	2,676	45.6	3,041	61,000	2.825
4350	105	HDY	A-MAX	39.6	2,563	44.0	2,912	59,200	2.825
4350	115	BAR	RN	39.6	2,498	44.0	2,839	62,500	2.825

243 Winchester Super Short Magnum									
Barrel: 24", Twist: 1-10"			Primer: WIN WLR		Bullet Diameter .243"				
4064	58	HDY	V-MAX	42.3	3,500	47.0	3,888	59,300	2.260
4064	75	HDY	V-MAX	38.7	3,112	43.0	3,458	62,700	2.310
4064	100	SIE	SPBT	35.0	2,660	39.0	2,961	63,600	2.310
2700	75	HDY	V-MAX	44.0	3,240	49.0	3,606	61,500	2.310
2700	100	SIE	SPBT	39.6	2,780	44.0	3,088	64,000	2.310
4350	75	HDY	V-MAX	41.5	3,050	46.0	3,358	62,500	2.310
4350	100	SIE	SPBT	40.0	2,805	44.0	3,050	61,000	2.310

257 Roberts									
Barrel: 24", Twist: 1-10"			Primer: FED 210		Bullet Diameter .257"				
2700	75	SIE	HP	43.7	3,048	46.0	3,243	44,800	2.745
2700	85	BAR	X	40.9	2,868	43.0	3,051	44,100	2.770
2700	90	SIE	HPBT	39.9	2,810	42.0	2,989	42,700	2.735
4350	75	HDY	V-MAX	42.3	2,866	47.0	3,257	43,600	2.745
4350	85	BAR	X	41.4	2,728	46.0	3,100	44,500	2.770
4350	90	SIE	HPBT	40.5	2,641	45.0	3,001	42,100	2.735
4350	100	BAR	X	36.9	2,410	41.0	2,739	42,700	2.760
4350	100	NOS	B-TIP	40.1	2,550	44.5	2,898	44,100	2.775
4350	117	SIE	SBT	38.7	2,376	43.0	2,700	44,100	2.775
3100	90	SIE	HPBT	45.0	2,689	50.0	3,056	44,000	2.735
3100	100	BAR	X	41.4	2,381	46.0	2,706	37,800	2.760
3100	100	NOS	B-TIP	44.1	2,520	49.0	2,864	39,900	2.775
3100	117	HDY	SST	43.2	2,408	48.0	2,736	43,700	2.775

25 Winchester Super Short Magnum									
Barrel: 24", Twist: 1-10"			Primer: WIN WLR		Bullet Diameter .257"				
4064	87	HDY	SP	40.0	3,033	44.5	3,370	62,900	2.213
4064	100	NOS	B-TIP	38.7	2,876	43.0	3,196	62,800	2.300
4064	100	BAR	TSX	37.8	2,837	42.0	3,153	61,000	2.242
4064	115	BAR	TSX	35.6	2,605	39.5	2,895	62,000	2.281
4064	117	HDY	SPBT	36.0	2,585	40.0	2,872	64,500	2.340
2700	87	HDY	SP	46.4	3,192	51.5	3,547	61,500	2.213
2700	100	NOS	B-TIP	43.7	2,982	48.5	3,313	64,800	2.300
2700	100	BAR	TSX	43.2	2,970	48.0	3,300	62,200	2.242
2700	115	BAR	TSX	40.0	2,700	44.5	3,010	63,300	2.281
2700	117	HDY	SPBT	41.4	2,750	46.0	3,056	63,900	2.340

25-06 Remington									
Barrel: 24", Twist: 1-10"			Primer: WIN WLR		Bullet Diameter .257"				
4350	75	HDY	V-MAX	53.1	3,326	59.0	3,780	61,400	3.065
4350	90	SIE	HPBT	48.6	3,055	54.0	3,472	62,900	3.075
3100	75	SIE	HP	54.0	3,154	60.0	3,585	57,900	3.065
3100	90	SIE	HP	50.9	2,965</				