



◆ Indicates most accurate load

.25-06 Remington

Bullet Weight: 80 gr **Case Trim Length:** 2.484" **S.D.** 0.173
Bullet Style: TTSX BT **Primer:** Fed 210 **B.C.** 0.316
COAL: 3.090" **Barrel Length:** 24"
Case: R-P **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ H4831SC	57.0	3396	62.0	3656	102
Hybrid 100V	52.5	3532	57.5	3814	101

Bullet Weight: 90 gr **Case Trim Length:** 2.484" **S.D.** 0.195
Bullet Style: Banded Solid Spitzer **Primer:** Fed GM210M **B.C.** 0.325
COAL: 3.155" **Barrel Length:** 24.00"
Case: W-W **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
RL 22	53.5	3261	58.5	3536	94
◆ Magnum	59.0	3297	64.0	3519	95

Bullet Weight: 100 gr **Case Trim Length:** 2.484" **S.D.** 0.216
Bullet Style: TSX BT **Primer:** Fed GM210M **B.C.** 0.336
COAL: 3.080" **Barrel Length:** 24"
Case: W-W **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ MagPro	55.5	3090	60.5	3323	90
RL 22	50.5	3101	55.5	3320	91

Bullet Weight: 115 gr **Case Trim Length:** 2.484" **S.D.** 0.249
Bullet Style: TSX FB **Primer:** Fed GM210M **B.C.** 0.335
COAL: 3.090" **Barrel Length:** 24"
Case: W-W **Twist Rate:** 1:10"

Powder	Minimum		Maximum		
	Charge (grains)	Velocity (fps)	Charge (grains)	Velocity (fps)	Load Density (%)
◆ H4831SC	47.0	2797	52.0	2996	88
Magnum	55.0	2969	60.0	3161	93