

PRODUCTS

RESOURCES

SUPPORT

INFORMATION

PROMOTIONS

## 25-06 Remington - 85 Grain

Caliber  
Diameter

Weight &amp; Style

Ballistic  
CoefficientSectional  
Density

Part #

THE ONLY BULLET THAT CAN BE CALLED  
**BALLISTIC TIP**  
VARMINT

25  
.257"

85Gr. Spitzer

0.184  
OAL 1.000

43004

COMBINED TECHNOLOGY®  
**BALLISTIC**  
SILVERTIP

25  
.257"

85Gr. Spitzer

0.184  
OAL 1.000

51045

**Case Type:****Cart. Max. OAL:****Primer Type:****Barrel Length/Make:****Barrel Twist:**

Winchester

3.250"

WLR

24" Wiseman

1-10"

**Powder Type:****Powder Charge  
Grains****Muzzle Velocity:  
F.P.S. / M.P.S. (Feet Per Second / Meters Per Second)****Load Density:  
(Volume)**

H4831sc

Max. 55.5

3408 / 1038

88%

53.5

3331 / 1015

85%

51.5\*

3257 / 992

82%

IMR4064

Max. 47.0

3410 / 1039

78%

45.0

3315 / 1010

75%

43.0\*

3220 / 981

72%

IMR4895

Max. 46.0

3450 / 1051

77%

44.0

3305 / 1007

73%

42.0\*

3160 / 963

70%

IMR4350

Max. 53.5

3450 / 1051

86%

51.5

3313 / 1009

83%

49.5\*

3175 / 967

80%



PRODUCTS

RESOURCES

SUPPORT

INFORMATION

PROMOTIONS

## 25-06 Remington - 100 Grain

Caliber  
Diameter

Weight &amp; Style

Ballistic  
CoefficientSectional  
Density

Part #

THE ONLY BULLET THAT CAN BE CALLED  
**BALLISTIC TIP**  
HUNTING

25  
.257"

100Gr. Spitzer

0.216  
OAL 1.115

25100

**PARTITION**  
The Benchmark for Hunting Bullets Since 1948

25  
.257"

100Gr. Spitzer

0.216  
OAL 1.035

16317

**Case Type:****Cart. Max. OAL:****Primer Type:****Barrel Length/Make:****Barrel Twist:**

Winchester

3.250"

WLR

24" Wiseman

1-10"

**Powder Type:****Powder Charge  
Grains****Muzzle Velocity:  
F.P.S. / M.P.S. (Feet Per Second / Meters Per Second)****Load Density:  
(Volume)**

IMR4320

Max. 42.0\*

3118 / 950

70%

40.0

2983 / 909

67%

38.0

2848 / 868

64%

IMR4064

Max. 41.5

3142 / 957

71%

39.5

2987 / 910

68%

37.5\*

2832 / 863

64%

IMR7828

Max. 56.5

3252 / 991

94%

54.5

3127 / 953

90%

52.5\*

3002 / 915

87%

Magnum

Max. 62.0

3265 / 995

98%

60.0\*

3172 / 966

95%

58.0

3079 / 938

92%



PRODUCTS

RESOURCES

SUPPORT

INFORMATION

PROMOTIONS

## 25-06 Remington - 110 Grain

Caliber  
Diameter

Weight &amp; Style

Ballistic  
CoefficientSectional  
Density

Part #

25  
.257"

110Gr. Spitzer

0.238  
OAL 1.195

53742

**Case Type:****Cart. Max. OAL:****Primer Type:****Barrel Length/Make:****Barrel Twist:**

Winchester

3.250"

WLR

24" Wiseman

1-10"

**Powder Type:****Powder Charge  
Grains****Muzzle Velocity:**

F.P.S. / M.P.S. (Feet Per Second / Meters Per Second)

**Load Density:  
(Volume)**

W760

Max. 46.5

3078 / 938

81%

44.5\*

2997 / 913

77%

42.5

2884 / 879

74%

H4831sc

Max. 51.0\*

3131 / 954

84%

49.0

2993 / 912

81%

47.0

2950 / 899

77%

IMR4831

Max. 51.0

3177 / 968

86%

49.0

3081 / 939

82%

47.0\*

2996 / 913

79%

IMR4350

Max. 49.5

3183 / 970

83%

47.5\*

3092 / 942

79%

45.5

2955 / 900

76%



PRODUCTS

RESOURCES

SUPPORT

INFORMATION

PROMOTIONS

## 25-06 Remington - 115 Grain

Caliber  
Diameter

Weight &amp; Style

Ballistic  
CoefficientSectional  
Density

Part #

25  
.257"

115Gr. Spitzer

0.249  
OAL 1.205

51050

25  
.257"

115Gr. Spitzer

0.249  
OAL 1.207

25115

25  
.257"

115Gr. Spitzer

0.249  
OAL 1.145

16318

Case Type:

Cart. Max. OAL:

Primer Type:

Barrel Length/Make:

Barrel Twist:

Winchester

3.250"

WLR

24" Wiseman

1-10"

Powder Type:

Powder Charge  
Grains

Muzzle Velocity:

F.P.S. / M.P.S. (Feet Per Second / Meters Per Second)

Load Density:  
(Volume)

IMR4064

Max. 40.0

2871 / 875

69%

38.0

2744 / 836

66%

36.0\*

2617 / 797

62%

RL19

Max. 50.0

3007 / 916

86%

48.0

2909 / 886

82%

46.0\*

2810 / 856

79%

IMR7828

Max. 54.0

3030 / 923

91%

52.0

2880 / 877

87%

50.0\*

2730 / 832

84%

A-3100

Max. 52.5

3047 / 928

90%

50.5

2966 / 904

87%

48.5\*

2884 / 879

83%



PRODUCTS

RESOURCES

SUPPORT

INFORMATION

PROMOTIONS

## 25-06 Remington - 120 Grain

Caliber  
Diameter

Weight &amp; Style

Ballistic  
CoefficientSectional  
Density

Part #

25  
.257"

120Gr. Spitzer

0.260  
OAL 1.175

35643

<b>Case Type:</b>	<b>Cart. Max. OAL:</b>	<b>Primer Type:</b>	<b>Barrel Length/Make:</b>	<b>Barrel Twist:</b>
Winchester	3.250"	WLR	24" Wiseman	1-10"

Powder Type:	Powder Charge Grains	Muzzle Velocity: F.P.S. / M.P.S. (Feet Per Second / Meters Per Second)	Load Density: (Volume)
IMR4064	Max. 40.0	2870 / 874	69%
	38.0	2740 / 835	66%
	36.0*	2610 / 795	62%
IMR4320	Max. 41.0*	2888 / 880	69%
	39.0	2773 / 845	66%
	37.0	2658 / 810	63%
RL19	Max. 50.0	2990 / 911	86%
	48.0	2890 / 880	82%
	46.0*	2790 / 850	79%
Viht N165	Max. 50.5	3007 / 916	88%
	48.5	2907 / 886	85%
	46.5*	2807 / 855	81%

