

- Winchester Smokeless Propellants - Rifle Data

RIFLE DATA

NEVER Exceed the Loads Listed Here

25-06 Remington

BBL: 24" PR: Remington 9 1/2
 TWIST: 1:10" TRIM: 2.484"
 CASE: Remington BULLET DIAM. .257"

Bullet	Powder	COL	Starting Charge Wt. (grs)	Velocity (fps)	Pressure	Max Charge Wt. (grs)	Velocity (fps)	Pressure
75 gr. HDY V-MAX	760	3.100"	51.0	3471	44,500 CUP	55.0	3626	50,100 CUP
85 gr. NOS BT	760	3.230"	48.0	3248	45,000 CUP	52.0	3443	50,600 CUP
87 gr. SPR HP	760	3.115"	47.0	3138	43,800 CUP	50.5	3327	51,100 CUP
90 gr. SIE HPBT	760	3.100"	47.0	3135	44,300 CUP	51.0	3315	50,200 CUP
100 gr. NOS PART	760	3.200"	42.0	2843	44,600 CUP	47.0	3059	50,700 CUP

25-06 Remington



- Trim To Length - 2.484"
- Maximum Overall Length with Bullet Seated - 3.250"
- Nominal Bullet Diameter (Jacketed) - .257"

Caliber	Charge	Weight	Velocity	Pressure
Bullet Weight & Type	Powder	(grs.)	(fps)	
100 grains SP	WXR	53.5	3210	58,500 psi
120 grains HPBT	WXR	50.7	2975	58,500 psi