

7 mm Remington Magnum

Case:Remington
Primer:Remington 9 1/2 M
Bullet:Hornady 120 grs Spire Pt.
Barrel:24"
C.O.L :3,29"

Powder	Load	Vel. ft/s	P.S.I. Cup
SR 4759	36,5	2695	51900
IMR 4227	37,0	2705	51300
IMR 4196	44,0	2980	51100
IMR 3031	52,5	3180	51200
IMR 4064	55,5	3245	51200
IMR 4895	54,5	3215	52000
IMR 4320	55,5	3185	51400
IMR 4350	65,0	3300	51400
IMR 4831	68,5	3335	51400

Case:Remington
Primer:Remington 9 1/2 M
Bullet:Remington 175 grs Core Lokt PSP
Barrel:24"
C.O.L.:3,29"

Powder	Load	Vel. ft/s	P.S.I. Cup
SR 4759	34,0	2220	51200
IMR 4227	35,5	2240	51800
IMR 4196	41,5	2440	52000
IMR 3031	47,5	2555	50700
IMR 4064	51,0	2645	51500
IMR 4895	50,0	2645	52000
IMR 4320	50,5	2665	52000
IMR 4350	59,5	2765	51800
IMR 4831	63,0	2790	52000
IMR 7828	66,0	2910	52000

Case:Remington
Primer:Federal 215
Bullet:Barnes 140 grs XBTLC
Barrel:24"

C.O.L.3,27"

Powder	Load	Vel. ft/s	P.S.I. Cup
IMR 4350	65,3	3060	58000
IMR 4831	66,5	3040	56000
IMR 7828	72,3C	3100	58000

Case:Remington
Primer:Federal 215
Bullet:Nosler 150 grs Ballistic Tip
Barrel:24"

C.O.L.:3,29"

Powder	Load	Vel. ft/s	P.S.I. Cup
IMR 4350	60,6	2940	56000
IMR 4831	63,2	2960	57000
IMR 7828	68,2	3000	57000

Case:Remington
Primer:Federal 215
Bullet:Swift Scirroco
150 grs
Barrel:24"
C.O.L.:3,27"

Powder	Load	Vel.	P.S.I.
IMR 4350	58,8	ft/s	Cup 56000
IMR 4831	62,0	2930	57000
IMR 7828	67,1	2940	56000
		2980	

Case:Remington
Primer:Federal 215
Bullet:Nosler 160 grs Partition
Barrel:24"
C.O.L.:3,29"

Powder	Load	Vel.	P.S.I.
IMR 4350	58,7	ft/s	Cup 57000
IMR 4831	60,2	2880	56000
IMR 7828	66,0	2860	57000
		2940	

Case:Remington
Primer:Federal 215
Bullet:Swift A-Frame
160 grs
Barrel:24" C.O.L.:3,25"

Powder	Load	Vel.	P.S.I.
IMR 7828	66,5	ft/s	Cup 59000
		2940	

Case:Remington
Primer : Fed 215
Bullet:150 grs Core Lokt PSP
Barrel:24"
C.O.L. : 3,29"

Powder	Load	Vel. Ft/s	P.S.I. Cup
SR 4759	35,0	2420	51500
IMR 4227	35,0	2455	51000
IMR 4198	43,0	2705	52000
IMR 3031	51,0	2850	52000
IMR 4064	54,0	2935	51600
IMR 4895	52,0	2880	51500
IMR 4320	54,0	2895	51300
IMR 4350	63,0	3010	51700
IMR 4831	66,5	3055	52000